

Downeast 37 Standard Equipment List

2020 Model Year

Length Overall	42' 6"	12.95 m
Hull Length	38' 2"	11.64 m
Beam (overall)	13' 3"	4.01 m
Draft	3' 7"	1.09 m
Displacement (full load)	22,100 lbs	11.05 T
Fuel	300 usg	1136 L
Water	120 usg	454 L
Holding	50 usg	189 L
Air Draft (w/mast)	11' 9"	3.58 m

Hull

- Back Cove white iso-npg gelcoat w/ vinylster backup resin
- VIP Resin Infused Hull w/ PVC foam core sandwich
- VIP Resin Infused foam core stringer system
- Advanced prop pocket hull design
- Awlgrip boot top
- Molded cove stripe depression w/ "gold or silver leaf" style stripe

Deck

- Back Cove white gelcoat w/graystone anti-skid on walking surfaces
- VIP Resin Infused core sandwich structure
- Mooring cleats forward, aft and spring line cleats.
- Molded Composite bow sprit w/ stainless steel anchor roller and windlass
- Anchor locker w/ ground tackle storage
- LED deck mounted running lights
- LED all-around anchor/ nav light on hard top
- Teak accent stripe on cabin side
- Custom 1-1/4" 316L stainless steel perimeter and cockpit rail
- SS handrails concealed under hardtop, port, and starboard
- Compressed air horn on hardtop (mast optional)
- (4) opening port lights w/ insect screens and shades
- Port & starboard molded steps leading to side and fore deck
- SureShade 'Silent Glide' cockpit awning system
- Transom door on centerline
- Swim platform w/ SS under-mount swim ladder
- Fridge in aft end of port helm deck settee
- Ice maker in aft end of starboard helm deck settee
- Port side helm deck settee converts to berth with filler cushion
- Rail mount gas grille with custom bracket
- Hot and cold cockpit shower
- Self draining cockpit
- Pop-up fender cleats on cockpit coamings

Mechanical Systems

- Cummins QSB 6.7 480 mhp electronic controlled engine w/ ZF gear
- 2.25" Aquamet shaft
- 4 Blade NiBrAl propeller
- PSS 'dripless' shaft log
- Binnacle mount electronic single lever engine control
- Raymarine digital engine display
- Bronze sea valve on engine intake
- Marelon sea valves on underwater thru hulls
- Bronze raw water strainer on engine, generator and AC intake
- Racor fuel/water separator
- Vented cross-linked polyethylene fuel tank with shut off valves
- 8" wet exhaust with dual-stage horizontal muffler
- Electric actuated trim tabs port and starboard w/ helm indicators
- SeaStar hydraulic steering w/ tilt helm pump
- Sidepower bow thruster w/ joystick control (SE80i)
- Hot and cold pressurized water
- 11 gallon water heater w/ heat exchanger, tempering valve and pressure relief valve plumbed to thru-hull
- Automatic Fireboy extinguisher system w/ manual back-up
- Battery powered salon and cabin smoke detectors
- Two zone air conditioning w/ reverse cycle heat

Electrical Systems

- AC/DC control panels with polarity indicator
- DC system battery management switching
- DC breakers for electronics
- Emergency battery bank cross-over switch (ACR)

- (2) 120Vac 30 amp shore power inlets w/50ft cords
- 120Vac shore power system ELCI protected
- Galvanic isolator
- Onan 7.5 KW genset with sound shield and water/exhaust separator
- GFI protected 120Vac circuits
- 40 Amp battery charger
- (2) 4D AGM house battery; (3) Group 31 AGM engine start battery
- (3) 12Vdc automatic bilge pumps
- Bonding system w/ zinc transom anode
- Mechanical/utility space lighting
- Cockpit courtesy lights switched at transom door and helm
- Cabin courtesy lights switched at helm and master SR berth
- Overhead LED lights w/ dimmer control in cabins, salon and cockpit
- Overhead bi-color LED light at helm station
- 12Vdc outlets throughout vessel

Head / Sanitary System

- Head w/ separate shower stall w/ bi-fold door
- Molded seat in shower stall w/ storage beneath
- Built-in vanity w/ sink
- Lewmar hatch w/ OCEANair Skyscreen
- Stainless steel opening port w/ insect screen and shade
- Cherry framed mirror
- Full length mirror on door
- Solid surface countertop
- Single lever faucet
- Shower-drain sump pump system
- Full size fresh water electric MSD w/ holding tank
- Waste and fresh water level gauge (in head)
- Macerator for holding tank overboard discharge as permitted
- Holding tank pump out fitting on deck
- Sealed overhead LED lighting (w/ dimmer control)
- Powered exhaust fan

Helm Deck / Salon Area

- Clear anodized aluminum windows w/ opening side and center windows
- (3) windshield wipers w/fresh water wash and intermittent control
- Lewmar sliding hatch w/ OCEANair Skyscreen
- Compass, illuminated
- 20" Stazo wood grain steering wheel
- Lleboc helm seat
- Adjustable, sloping footrests at both helm seats
- Large bilge storage below helm sole, access by gas strut assisted hatch
- Large engine room hatch
- Settee to port and settee to starboard
- Headliner with padded panels
- SiriusXM ready Fusion stereo (w/ Bluetooth and NMEA 2k connectivity)
- 6 inch, 200 Watt Fusion speakers
- Charging station (AC/DC/USB)
- Port and starboard aft cockpit seating

Lower Galley

- Electric two burner cook-top with pop-ups
- AC/DC stainless steel, drawer-type fridge/freezer compartments
- Large SS galley sink w/ single lever faucet & drop in cover
- Solid surface countertop
- Convection microwave
- Drawer and doors storage below counter
- "Teak and Holly" high pressure laminate sole w/ surface texture

Master Stateroom

- Herreshoff style interior accommodation
- Lewmar hatch w/ OCEANair Skyscreen
- "Teak and Holly" high pressure laminate sole w/ surface texture
- Headliner with padded panels
- Island queen berth w/ drawers and storage below
- 8" polyurethane/latex mattress
- Lockers outboard
- Cedar lined hanging locker to starboard
- Multi drawer bureau w/ dovetailed drawers to port
- Charging station (AC/DC/USB)
- 6 inch, 200 Watt Fusion speakers